VIDEO DISTRIBUTION

DIGITAL CATV SPLITTERS HORIZONTAL

PERFECT VISION 2 WAY SPLITTER

DESCRIPTION:

- SCTE compliant F-port
- Soldered back cover to get 130 dB RFI shielding
- Capacitor coupled
- Low insertion loss
- High return loss and isolations

PVSP1G-2W

PERFECT VISION 3 WAY BALANCED SPLITTER

DESCRIPTION:

- SCTE compliant F-port
- Soldered back cover to get 130 dB RFI shielding
- Capacitor coupled
- Low insertion loss
- High return loss and isolations

PVSP1G-3WB

PERFECT VISION 4 WAY SPLITTER

DESCRIPTION:

- SCTE compliant F-port
- Soldered back cover to get 130 dB RFI shielding
- Capacitor coupled
- Low insertion loss
- High return loss and isolations

PVSP1G-4W

PERFECT VISION 3 WAY SPLITTER

DESCRIPTION:

- SCTE compliant F-port
- Soldered back cover to get 130 dB RFI shielding
- Capacitor coupled
- Low insertion loss
- High return loss and isolations

PVSP1G-3W

	PART NUMBER	PARAMETERS (UNIT)	FREQUENCY RANGE (MHZ)	INSERTION LOSS (MAX. DB)	INPUT RETURN LOSS (MIN. DB)	OUTPUT RETURN LOSS (MIN. DB)	ISOLATION (MIN. DB)	PORT IMPEDANCE (Ω)	RFI SHIELDING (DB)
HORIZONTAL	PVSP1G-2W	2-way	5-1000	4	20	20	25	75	130
	PVSP1G-3W	3-way Unbalanced	5-1000	4.0/8.0	20	20	25	75	130
	PVSP1G-3WB	3-way Balanced	5-1000	7	20	20	25	75	130
	PVSP1G-4W	4-way	5-1000	8	20	20	25	75	130